


Features

- Glass passivated junction
- Moisture sensitivity: level 1, per J-STD-020
- Solder dip 260 °C, 10 s
- Low profile, typical thickness 1.0mm
- Polarity: Uni-directional
- Excellent clamping capability and Fast response time
- 200W peak pulse power capability with a 10/1000us waveform
- AEC-Q101 qualified



RoHS
COMPLIANT



eSGA
(SOD-123FL)

Typical Applications

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting on Ics, MOSFET, signal lines of sensor units for consumer, computer, industrial, automotive and telecommunication.

Maximum Ratings (TA = 25 °C unless otherwise noted)			
Parameter	Symbol	Value	Unit
Peak power dissipation with a 10/1000us waveform	$P_{PPM}^{1)}$	Minimum 200	W
Peak pulse current with a 10/1000us waveform	$I_{PPM}^{1)}$	See Next Table	A
Steady state power dissipation on infinite heatsink	$P_{M(AV)}^{2)}$	0.5	W
Peak forward surge current, 8.3ms single half sine-wave uni-directional only	I_{FSM}	30.0	A
Maximum instantaneous forward voltage at 25A	V_F	3.5	V
Thermal resistance junction to ambient air	R_{thja}	85	°C/W
Operating junction and storage temperature range	TJ, TSTG	-65 to +150	°C

Notes:

1) Non-repetitive current, per fig.3 and derated above TA=25°C per fig.4.

2) Power dissipation mounted on recommended pad layout

3) Thermal resistance from junction to ambient, mounted on PCB with 5.0×5.0mm copper pads



AF2TVS10A thru AF2TVS36A

Surface Mount Transient Voltage Suppressors
 Peak Pulse Power 200W Stand-off Voltage 10 to 36V

Electrical Characteristics (TA = 25 °C unless otherwise noted)								
Part Number	Marking Code	Reverse Stand-off Voltage	Breakdown Voltage		Test Current	Max Reverse Leakage Current	Max. Clamp Voltage	Peak Pulse Current
		VRWM	VBR @ IT		IT	IR @ VRWM	Vc @ IPP	IPP
			Min	Max				
		V	V	V				
AF2TVS10A	A210	10	11.1	12.3	1	5	17	11.8
AF2TVS11A	A211	11	12.2	13.5	1	5	18.2	11
AF2TVS12A	A212	12	13.3	14.7	1	5	19.9	10.1
AF2TVS13A	A213	13	14.4	15.9	1	5	21.5	9.3
AF2TVS14A	A214	14	15.6	17.2	1	5	23.2	8.62
AF2TVS15A	A215	15	16.7	18.5	1	5	24.4	8.2
AF2TVS16A	A216	16	17.8	19.7	1	5	26	7.69
AF2TVS17A	A217	17	18.9	20.9	1	5	27.6	7.25
AF2TVS18A	A218	18	20	22.1	1	5	29.2	6.85
AF2TVS20A	A220	20	22.2	24.5	1	5	32.4	6.17
AF2TVS22A	A222	22	24.4	26.9	1	5	35.5	5.63
AF2TVS24A	A224	24	26.7	29.5	1	5	38.9	5.14
AF2TVS26A	A226	26	28.9	31.9	1	5	42.1	4.75
AF2TVS28A	A228	28	31.1	34.4	1	5	45.4	4.41
AF2TVS30A	A230	30	33.3	36.8	1	5	48.4	4.13
AF2TVS33A	A233	33	36.7	40.6	1	5	53.3	3.75
AF2TVS36A	A236	36	40	44.2	1	5	58.1	3.44



AF2TVS10A thru AF2TVS36A

Surface Mount Transient Voltage Suppressors
 Peak Pulse Power 200W Stand-off Voltage 10 to 36V

Ratings and Characteristics Curves

(TA = 25°C unless otherwise noted)




Figure 1. Typical Instantaneous Forward Characteristics




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Pulse Waveform




Figure 4. Peak Pulse Power Derating Curve




Figure 5. Peak Pulse Power Derating Curve

Package Outline Dimensions

in inches (millimeters)



HE

DM	Unit: mm	Unit: inch





AF2TVS10A thru AF2TVS36A


Surface Mount Transient Voltage Suppressors
Peak Pulse Power 200W Stand-off Voltage 10 to 36V



	M N	MAX	M N	MAX
A	0.9	1.08	0.035	0.043
A1	0	0.1	0.000	0.004
B	0.85	1.05	0.033	0.041
C	0.1	0.25	0.004	0.010
D	1.7	2	0.067	0.079
E	2.9	3.1	0.114	0.122
L	0.43	0.83	0.017	0.033
HE	3.5	3.9	0.138	0.154



Soldering footprint




Packing Information

Packing quantities:

3000 pcs/Reel, 40 Reels/Box; 8mm Tape, 7" Reel

Tape & Reel Specification



Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-



AF2TVS10A thru AF2TVS36A

Surface Mount Transient Voltage Suppressors
Peak Pulse Power 200W Stand-off Voltage 10 to 36V

Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.